



# pH/ORP -TX - 22

## pH/ORP TRANSMITTER

### Features

- Electrode with transmitter
- pH or ORP Measurement
- 1" NPT (M) Process Connections
- Designed for Flow Through and Submersion Applications
- Suitable for High Temperature Use
- Compact Design

### Description

**E**lectronet series PH/ORP-TX-22 transmitter is designed for use in general purpose water applications. The large volume single junction reference cell coupled with the non-fouling porous Teflon liquid junction assures a long life in general service.



### Technical Specifications

Measuring Range	0 to 14 pH
Response Time @ 25°C (77°F)	95% of reading in 10 seconds
Body Material	Ryton
O-Rings	Viton
Output	4 to 20 mA
Output Load	Max 600 Ω
Power Supply	24V DC, External
Safe Operating Voltage	36VDC
Temperature Range	1) -5 to 80°C (23 to 176°F) Standard Version 2) 25 to 110°C (77 to 230°F) High Temp Version
Pressure Range	0 to 6.9 bar (0 to 100 psi)
Drift	< 2.0 mV/week
pH Glass Bulb Impedance @ 25°C (77°F)	80 MegaOhms (Standard Version), 150 MegaOhms (High Temp Version)
Mounting	Insertion (Screw-in)

### Ordering Information

**Sample Order Code : 66N**

Parameter	Code	Value
66 Process Connection	66M	¾" NPT Threaded
	66N	1" ASA 150 Flanged
	66O	1" Tri Clover
	66X	Other

Note : ▪ Due to our continuous product revisions, design specification and model numbers are subject to change without notice.  
▪ Accuracy defined at Lab Conditions.  
▪ For other requirement please consult factory.

### ELECTRONET EQUIPMENTS PVT. LTD.

**Factory Address:**

Plot No. 8, (SEZ) Phase 1, Kesurdi MIDC,  
Khandala, Dist.- Satara  
Pin: 412 801, Maharashtra, India.

**Registered Office:**

Plot No. 84, 85, 86, Tiny Industrial Estate,  
Kondhwa Budruk,  
Pune-411 048, Maharashtra, India.

+91-20-26931476/2039    ho@eeplindia.com    +91-20-26934122    www.eeplindia.com