



pH/ORP -TX - 22

pH/ORP TRANSMITTER

Features

- Electrode with transmitter
- pH or ORP Measurement
- 1" NPT (M) Process Connections
- Designed for Flow Through and Submersion Applications
- Suitable for High Temperature Use
- Compact Design

Description

Electronet series PH/ORP-TX-22 transmitter is designed for use in general purpose water applications. The large volume single junction reference cell coupled with the non-fouling porous Teflon liquid junction assures a long life in general service.



Technical Specifications

Measuring Range	0 to 14 pH
Response Time @ 25°C (77°F)	95% of reading in 10 seconds
Body Material	Ryton
O-Rings	Viton
Output	4 to 20 mA
Output Load	Max 600 Ω
Power Supply	24V DC, External
Safe Operating Voltage	36VDC
Temperature Range	1) -5 to 80°C (23 to 176°F) Standard Version 2) 25 to 110°C (77 to 230°F) High Temp Version
Pressure Range	0 to 6.9 bar (0 to 100 psi)
Drift	< 2.0 mV/week
pH Glass Bulb Impedance @ 25°C (77°F)	80 MegaOhms (Standard Version), 150 MegaOhms (High Temp Version)
Mounting	Insertion (Screw-in)

Ordering Information

Parameter	Code	Value
66 Process Connection	66M	¾" NPT Threaded
	66N	1" ASA 150 Flanged
	66O	1" Tri Clover
	66X	Other

66

Note : ▪ Due to our continuous product revisions, design specification and model numbers are subject to change without notice.
▪ Accuracy defined at Lab Conditions.
▪ For other requirement please consult factory.

ELECTRONET EQUIPMENTS PVT. LTD.

Factory Address:

Plot No. 8, (SEZ) Phase 1, Kesurdi MIDC,
Khandala, Dist.- Satara
Pin: 412 801, Maharashtra, India.

Registered Office:

Plot No. 84, 85, 86, Tiny Industrial Estate,
Kondhwa Budruk,
Pune-411 048, Maharashtra, India.

USA Office:

IntelliComponents, Inc.
710 Dacula Rd., Ste 4A-200,
Atlanta, GA 30019



+91-20-26931476/2039



ho@eplindia.com



+91-20-26934122



www.eplindia.com



(678)-720-3030



info@intellcomponentsinc.com